TRIBUNE

FULL HEIGHT ULTRA SECURE SINGLE READER TURNSTILE





Who you want, When you want!



Turney[™] is a member of the Turnstar family

- The TRIBUNE provides the highest levels of security available in a turnstile
- 100% validated entry and exit transactions
- Only one reader required for bi-directional access
- Exported worldwide

APPLICATIONS	 Suited for applications requiring the strictest controls over access and time & attendance Used extensively in applications such as mines, factories and warehouses Ideal for integration with any biometric reader system
DESIGNED FOR	Interior and exterior installationsSevere operating conditions
AVAILABLE CONFIGURATIONS	• 4 arm (90°) • Single







What do you need to know when buying a turnstile?



In terms of the price, is the turnstile supplied complete or are there any hidden extras?

Tumstar units are supplied 100% complete. Control panels are ready for power and data connections. Reader mounting brackets are available for full height turnstiles for the mounting of access readers, ticketing equipment, pushbuttons and coin or token acceptors.



What are the running costs?

With a long-established reputation for being exceptionally reliable and durable, Tumstar turnstiles are built to give years of cost-free and fault-free service with no routine maintenance. Our products are a flt-and-forget solution.



Is this turnstile robust enough for the job? Am I going to have failures during service?

Tumstar products are designed for the harshest of environments and have become the standard for Afrtca's mining industry, which is known for extreme operating conditions. Production is carried out by state-of-the-art CNC machinery and robotic welding, all of which provide products of the highest quality and to the tightest of tolerances.



How long is the guarantee and is this an extra cost?

Turnstar's industry leading Five-Year Guarantee is included in the purchase price.



What does the guarantee cover?

All mechanical components, including ratchet disk and locking pawls, are covered by the Turnstar Five-Year Guarantee. The control panel, microswitches and solenoids are covered by a one-year guarantee.



Can you trust the turnstile supplier?

Established in 1990, Turnstar has manufactured and sold over 20 000 turnstiles. Our customers range from the world's largest blue chip corporations to single-site retailers. As one of the world's leading manufacturers, we have an unrivalled reputation for outstanding products backed by superior customer service.



Will the turnstile work with all types of access systems?

Turnstar turnstiles operate with all forms of electronic access control, ticketing and time & attendance systems. In addition, they can be operated with pushbutton controls, remote transmitters and coin or token acceptors.



What will happen to the turnstile in the event of a power failure?

The turnstile can be factory-set for either fall-secure (auto-lock on power failure) or fall-safe (auto-unlock on power failure) operation. The turnstile can also be unlocked by means of the mechanical key override which is supplied standard with the turnstile. A battery backup system is also available on request, which will provide normal operation under conditions of no power.



What other products are available with the turnstile

Turnstar manufactures pedestrian gates and security banners for use with all our turnstiles. We also supply special colours, and manufacture turnstiles in custom sizes and designs.



Where can I find out more about the unbeatable value from Turnstar?

Go to www.turnstar.co.za for more information on our product range, projects and client base.









Unique features of the TRIBUNE turnstile range

ROTALOK® ROTATION LOCKING MECHANISM

- Fitted to all TRIBUNE turnstiles
- Ultra heavy-duty electromechanical rotation locking mechanism
- Bi-directional operation
- Designed by professional engineers
- Tried, tested and perfected over a period of more than 20 years

RELIABLE



TECHNOLOGY

- Suspended rotor technology eliminating stress on the base bearing
- Self-centering rotation system rotor returns to starting position after every rotation
- Shock absorbing rubber coupling system
- Programmable PLC logic with user diagnostic features
- Mechanical key override clockwise and anticlockwise directions

DURABLE



FEATURES

- · Zinc plated for corrosion resistance
- · Ultra quiet, buffered solenoids and pawls
- Solenoids rated for 100% duty cycle
- · Case hardened locking disk and pawls eliminating any wear
- · Factory settings need no further adjustment
- No routine maintenance whatsoever, ever

GUARANTEED



MANUFACTURED TO LAST

- 5 year mechanical guarantee
- 1 year electrical guarantee

ROTRUN® PERPETUAL BASE BEARING

• Fitted to all TRIBUNE turnstiles

RELIABLE



TECHNOLOGY

• Combination of stainless steel and self-lubricating engineering plastics

DURABLE



FEATURES

- Designed for the harshest of conditions
- 100% corrosion resistant
- Unaffected by dust, dirt or moisture
- Self-lubricating

GUARANTEED



MANUFACTURED TO LAST

- Zero maintenance
- 5 year guarantee

Technical specifications

POWER	220 Volt AC (110 Volt AC on request)					
FREQUENCY	50Hz / 60Hz					
POWER CONSUMPTION	50W					
SOLENOID VOLTAGE	24 Volt DC (12 Volt DC on request)					
LOGIC VOLTAGE	24 Volt DC					
DIMENSIONS	• 1 700mm wide x 2 125mm high					
	1 730mm wide x 2 250mm high - recommended minimum opening size					
ROTOR DIAMETER	1 200mm					
ROTOR ARM	4 arm (90°)					
CONFIGURATION						
ROTOR ARMS	50mm diameter tube arms					
WEIGHT	220kg					
DESIGN	Modular bolt-together design for ease of transport and installation					
	Can be packed in broken-down form either onto a pallet or into a crate for transport					
SYSTEMS INTEGRATION	Integrates with all access control and time & attendance systems					
	Unlocking for entry / exit rotation controlled through normally open dry contact					
	Transaction / Rotation complete output					
	Integral wireways with draw wires in place – no exposed wires					

Key features supplied as standard


BATTERY BACKUP	Battery backup with two 12 volt 7Ah batteries connected in series providing up to 1 000 transactions
OVERHEAD BARRIER	Anti-climb protection - preventing pedestrians from climbing out of the turnstile when in the read position
TUBE SPACING	Tube arms are spaced 50mm apart at reader height to physically prevent biometric clocking from outside the turnstile
RECESSED READER MOUNTING	Physically prevents biometric clocking from outside the turnstile and provides the reader with protection from the elements

Manufacturing options

ROTATION	Electrically controlled bi-directional rotation (factory standard)					
LOCKING	Fail-secure auto-lock on power failure (factory standard)					
FIRE ALARM	Free rotation when triggered indefinitely					
SPECIAL PHYSICAL DESIGN OPTIONS	 Restrictor tubes for increased security Special split cover for low ceilings Special internal mechanism dust cover for dirty environments Heavy-duty base for portability (with forklift channels) 					
ACCESSORY OPTIONS	 LED red circle & green circle indicator light mounted in reader box LCD transaction counter with reset key switch Random search device Low energy light on underside of channel 					
FINISH OPTIONS	 Mild steel with UV resistant polyester exterior powder coat finish (charcoal blue hammertone) □ Mild steel with hot dip galvanised finish △ 304 grade brushed stainless steel 316 grade brushed stainless steel △ △ suitable for corrosive environments (details available on request) □ other colours available on request 					

STAR QUALITIES


- 1 Rotalok® rotation locking mechanism and electronic control panel
 - Incorporates: Anti-Trap® safety system
 - Suspended Rotor technology
- 2 Lockable top cover
- 3 Mechanical key override
- 4 Shock absorbing rubber coupling
- 5 50mm diameter tube arms spaced 50mm apart
- 6 Cycle start pushbutton
- 7 Secure reader mounting position
- 8 Rotarun® perpetual base bearing
- 9 Wiring side entry point
- 10 Wiring bottom entry point
- 11 Floor bolting positions 7 Off
- 12 Wall bolting position 1 Off






OPERATING CYCLE

STEP 1: PUSHBUTTON IS PRESSED TO ALLOW ENTRANCE INTO THE LOCKED TURNSTILE





STEP 2: READER IS ACCESSED AND RECOGNITION TAKES PLACE



STEP 3A: READER CONFIRMATION - ACCESS ALLOWED
TURNSTILE ROTATES A FURTHER 90° AND RELOCKS











TRIBUNE RANGE

TRIBUNE SINGLE								
А	Recommended opening width	1 730mm	С	Recommended opening height	2 250mm			
В	Turnstile width	1 700mm	D	Turnstile height	2 125mm			
				Headroom	1 986mm			







\$

MAXIMUM SECURITY OPTION

- RESTRICTOR TUBES can be welded to the turnstile rotor in order to limit the amount of space available in the quadrant. This addition increases the level of difficulty for two pedestrians to go through the turnstile together.
- The RESTRICTOR TUBE is supplied in matching finish to the turnstile.







© Turnstar Systems 2011

SPECIFICATION FOR ARCHITECTS AND SPECIFIERS

TURNSTAR TRIBUNE full height ultra secure single reader turnstile complete with anti-climb overhead barrier and battery backup, in finish (as mentioned on page 4).

Due to our policy of continuous improvement, products are subject to change without notice. Custom designs are available on request.

- Sole supplier of turnstiles to the ICC Cricket World Cup 2003
- Sole supplier of turnstiles to the CAF African Cup of Nations, Ghana 2008
- Sole supplier of turnstiles to the Green Point, Spccer City, Ellis Park,
 Loftus Versveld, Royal Bafokeng, Bloemfontein, Nelspruit and Polokwane
 South African National Football Stadiums



Turnstar Systems CC Reg No 1990/011871/23 17, 5th Street, Wynberg, Sandton, 2090, South Africa PO Box 41, Highlands North, 2037

Tel 0861 TURNSTAR / TURNSTILE

Tel $+27(0)11\ 786\ 1633\ /$ Tel $+27(0)11\ 021\ 8669\ /$ Fax $+27(0)11\ 440\ 5839$