TRIDENT

WAIST HEIGHT SINGLE AND DOUBLE TURNSTILE



We cover all the ins and outs



Tridey" is a member of the Turnstar family





- With a wide range of applications, The TRIDENT is the biggest selling waist height turnstile in Africa
- The TRIDENT is suitable for both prestige and industrial installations

TRIDENT SINGLE

- Designed for high speed ultra quiet operation
- Exported worldwide

APPLICATIONS	 Suited for applications requiring high volume access and medium levels of security Used extensively in applications such as office reception areas, health clubs, colleges, libraries, leisure parks and stadiums
DESIGNED FOR	Interior and exterior installationsSevere operating conditions
AVAILABLE CONFIGURATIONS	TRIDENT Single TRIDENT Double







Unique features of the TRIDENT turnstile range

ROTALOK® ROTATION LOCKING MECHANISM

- Fitted to all TRIDENT turnstiles
- Ultra heavy-duty electromechanical rotation locking mechanism
- Bi-directional operation
- Designed by professional engineers
- Tried, tested and perfected over a period of more than 20 years

RELIABLE



TECHNOLOGY

- Self-centering rotation system rotor returns to starting position after every rotation
- Anti-trap® safety system no mid-rotation locking or trapping in the event of a power failure
- Extra secure 60° anti-reverse system
- Programmable PLC logic with user diagnostic features
- Mechanical key override clockwise and anticlockwise directions

DURABLE



FEATURES

- · Zinc plated for corrosion resistance
- Ultra quiet, buffered solenoids and pawls
- · Solenoids rated for 100% duty cycle
- Case hardened locking disk and pawls eliminating any wear
- Factory settings need no further adjustment
- No routine maintenance whatsoever, ever

GUARANTEED



MANUFACTURED TO LAST

- 5 year mechanical guarantee
- 1 year electrical guarantee

ROTASLO® HYDRAULIC DAMPING SYSTEM

• Fitted to all TRIDENT turnstiles

RELIABLE



TECHNOLOGY

- Consistently smooth rotation
- Ultra quiet operation

DURABLE



FEATURES

· Low mechanical stress

GUARANTEED



MANUFACTURED TO LAST

• 1 year guarantee

Technical Specifications

POWER	220 Volt AC (110 Volt AC on request)
FREQUENCY	50Hz / 60Hz
POWER CONSUMPTION	50W (single turnstile) / 100W (double turnstile)
SOLENOID VOLTAGE	24 Volt DC (12 Volt DC on request)
LOGIC VOLTAGE	24 Volt DC
DIMENSIONS	See overleaf
ROTOR ARMS	38mm diameter stainless steel fixed tube arms
WEIGHT	TRIDENT Single 68kg
	TRIDENT Double 114kg
DESIGN	Modular bolt-together design for ease of transport and installation. Components can pass through
	a standard door. Can be packed in broken-down form either onto a pallet or into a crate for transport
SYSTEMS INTEGRATION	 Integrates with all access control and time & attendance systems
	 Unlocking for entry / exit rotation controlled through normally open dry contact
	Transaction / Rotation complete output
	Integral wireways with draw wires in place – no exposed wires

Manufacturing options

ROTATION OPTIONS	Electrically controlled bi-directional rotation (factory standard)
	Mechanically controlled uni-directional rotation by means of key override
	Free rotation
LOCKING OPTIONS	Fail-secure auto-lock on power failure (factory standard)
	Fail-safe auto-unlock on power failure
	Each direction of rotation configurable for either fail-secure or fail-safe operation
FIRE ALARM OPTIONS	Free rotation when triggered indefinitely (logic programmed for either direction of rotation
	on request)
POWER OPTIONS	Battery backup with two 12 volt 7Ah batteries connected in series
	o Up to 1 000 transactions in fail-secure mode
	o Up to 60 minutes operation in fail-safe mode
ACCESSORY OPTIONS	600mm stainless steel and glass turnstile screen
	Single / Double pushbutton in plastic housing
	LED red cross & green arrow indicator light
	Multiple coin acceptor for pay-for-entry systems
	LCD transaction counter with reset key switch
	Random search device
CABINET FINISH	Mild steel with UV resistant polyester exterior powder coat finish
OPTIONS	(charcoal blue hammertone) 🗖
	304 grade brushed stainless steel
	316 grade brushed stainless steel △
	△ suitable for corrosive environments (details available on request)
	other colours available on request
TOP COVER OPTIONS	Rustenburg granite top cover
	Stainless steel top cover
	J

STAR INSTALLATIONS










TRIDENT RANGE


TRIDENT SINGLE









TRIDENT DOUBLE







© Turnstar Systems 2011



STAR QUALITIES

- 1 Rotalok® rotation locking mechanism and electronic control panel
 - Incorporates:
- Rotaslo[®] hydraulic damping
- Mechanical key override (for free rotation)
- 2 Lockable Rustenburg granite or stainless steel top cover
- 3 Lockable bottom cabinet
- 4 38mm diameter stainless steel fixed tube arms
- 5 Access control reader mounting position
- 6 Wiring bottom entry point
- 7 Floor bolting positions









Turnstar Systems (Pty) Ltd | Reg No: 2012/100536/07 | Established in 1990

Johannesburg Head Office:

18 6th Street, Wynberg, Sandton, 2090 PO Box 41, Highlands North, 2037

T: +27 (0)11 786 1633

F: +27 (0)11 440 5839

Cape Town Office:

Unit 9 Elect Park, 13 Teejay Street, Brakenfell, Cape Town

T: +27 (0)21 981 3043

info@turnstar.co.za www.turnstar.co.za